

**TCB**

**GRANT OF EQUIPMENT  
AUTHORIZATION**

**TCB**

**Certification  
Issued Under the Authority of the  
Federal Communications Commission  
By:**

**American TCB, Inc.  
6731 Whittier Avenue Suite C110  
McLean, VA 22101**

**Date of Grant: 04/13/2010  
Application Dated: 04/13/2010**

**KANNAD  
Z.I. des Cinq Chemins  
Guidel, 56520  
France**

**Attention: Stephane Jincheleau**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER: VIQ-SAFELINK2**

**Name of Grantee: KANNAD**

**Equipment Class: 406 MHz EPIRB**

**Notes: SafeLink Distress Beacon**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
GM	80.1101(c)(5)	406.037 - 406.037	5.0	1000.0 Hz	16K0G1D
GM	80.1101(c)(5)	121.5 - 121.5	0.05	3000.0 Hz	3K20A3X

The KANNAD SafeLink Manual+ is a COSPAS-SARSAT Class 2, 406 MHz distress beacon. The KANNAD SafeLink Manual+ is equipped with a non-Float-Free container and is designated as RTCM Category 2 EPIRB with GPS position broadcast.

GM: This unit meets requirements for GMDSS use as contained in Subpart W of Part 80.

